



Florigo ultra-clean<sup>WT</sup> 3 removes clay shells, sand and soil from potatoes and other root vegetables thoroughly and without damaging them. The Florigo ultra-clean<sup>WT</sup> 3 pairs with the Florigo ultra-clean<sup>OC</sup> 3 to form a cleaning system that is well suited for high-capacity lines and requires little maintenance.

## BENEFITS



Simplifies cleaning of the drum and cleans product efficiently and evenly without damage.



Cleans product thoroughly, including curves and grooves.



Optimises retention time and controls cleaning based on amount of soil on the product.



Easy to maintain with only a single access point to apply grease.

## STANDARD FEATURES

- Different shaped profiles in the drum for specific products
- Spray pipe mounted inside and outside the drum
- Adjustable slide gate that regulates the retention time of the product in the drum washer
- Frequency controller on drum drive
- Sturdy support wheels design
- Centralised greasing point
- Stainless steel execution (exception fans, pumps, drives, valves, bearings, belts)

## OPTIONAL FEATURES

- Rotary brush mounted inside the drum
- Reclaimer with pump

## APPLICATIONS

- french fries
- snacks

## SPECIFICATIONS

Florigo ultra-clean® WT 3							
model name	WT 2000-08	WT 3000-08	WT 2000-12	WT 3000-12	WT 3000-15	WT 4000-12	WT 4000-15
capacity kg/hr (lbs/hr)	7000 (15400)	10000 (22000)	13000 (28600)	17000 (37450)	28000 (61700)	28000 (61700)	40000 (88190)
motor drum kW (hp)	3 (4)				4.4 (6)		
motor brush kW (hp)	2.2 (3)				3 (4)		
water consumption refreshment m <sup>3</sup> /1000kg/hr (cfm/2205lbs)	0.5 (18)						
length mm (in)	3850 (152)	4850 (191)	3850 (152)	4850 (191)		5850 (230)	
width mm (in)	1400 (55)		1800 (71)		2100 (83)	1800 (71)	2100 (83)
height mm (in)	2050 (80)		2450 (96)		2750 (108)	2450 (96)	2750 (108)
empty weight kg (lbs)	1700 (3748)	2100 (4630)		2500 (5512)	2800 (6173)	2900 (6394)	3200 (7055)
operation weight kg (lbs)	2100 (4630)	2500 (5512)		2900 (6394)	3200 (7055)	3300 (7276)	3600 (7938)

all above specifications are subject to change and may differ according to the product, please confirm when placing your order.

TO FIND OUT HOW YOU AND YOUR TEAM CAN GET THE MOST FROM YOUR TNA SOLUTIONS, CONTACT US

TNA Australia Pty Ltd, 24 Carter Street, Sydney Olympic Park NSW 2127, Australia Tel +61 2 9714 2300 Fax +61 297 482 970 [tnasolutions.com](http://tnasolutions.com) [info@tnasolutions.com](mailto:info@tnasolutions.com)